















## SPECIFICATIONS

	<b>GEOLOGY</b>	Limestone
	<b>TYPE</b>	100% Bedface
	<b>PATTERN</b>	2:1 Sawn Course Heights   Dimensional Ashlar
	<b>HEIGHTS</b>	2.25", 5"
	<b>LENGTHS</b>	6" - 20" (Crated or palletized material can exceed 20")
	<b>DEPTHS</b>	Thin Veneer: .75" - 1.25"   Full Veneer: 3" - 5"
	<b>COLORS</b>	Mix of Grays, Buff, Beige
	<b>COVERAGE</b>	Full Veneer: 35-40 Sq Ft per Ton
	<b>WEIGHT</b>	~13.7 lbs per Sq Ft (Thin Veneer)
	<b>FLATS</b>	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 200 s/f Pallet
	<b>CORNERS</b>	10 Ln/Ft Box; 100 Ln/Ft Crate; 100 Ln/Ft Pallet
	<b>NOTES</b>	<b>NEW</b> (Same as <b>Fond du Lac Dimensional</b> but with 2 heights: 2.25" & 5")

### ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

### ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

### ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

### ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730



**GOLD QUARRIER**  
ANSI/NSC 373-2013  
C0290908-101



**GOLD FABRICATOR**  
ANSI/NSC 373-2013  
C0289215-101