















SPECIFICATIONS

| | | |
|--|-----------------|---|
|  | GEOLOGY | Sandstone |
|  | TYPE | 100% Splitface |
|  | PATTERN | Coursed Dimensional Ashlar 2:1 Dimensional Ashlar |
|  | HEIGHTS | 2-1/4" (20%), 5" (50%), 7-3/4" (30%) |
|  | LENGTHS | Thin Veneer: 8"-20"; Full Bed-Depth: 8" - 36" |
|  | DEPTHS | Thin Veneer: 3/4" to 1-1/4"; Full Bed-Depth: 3" - 5" |
|  | COLORS | Beige, Brown, Buff, Salmon, Tan |
|  | COVERAGE | 35-40 sf per ton (Full Bed-Depth) |
|  | WEIGHT | 12.3 lbs. per square foot (Thin Veneer) |
|  | FLATS | 10 s/f Box, 100 s/f Crate, 180 s/f Crate |
|  | CORNERS | 10 l/f Box, 100 l/f Crate; Crated material can exceed 20" |
|  | NOTES | |

ASTM C-97

| | |
|-----------------------|-----|
| Water Absorption % | 3.8 |
| Bulk Specific Gravity | 2.4 |

ASTM C-170

| | |
|----------------------------------|------|
| Parallel to Rift, Dry (psi) | 4115 |
| Parallel to Rift, Wet (psi) | 2612 |
| Perpendicular to Rift, Dry (psi) | |
| Perpendicular to Rift, Wet (psi) | |

ASTM C-99

| | |
|-----------------------------|------|
| Parallel to Rift, Dry (psi) | 1912 |
| Parallel to Rift, Wet (psi) | 2054 |

ASTM C-880

| | |
|----------------------------------|-----|
| Perpendicular to Rift, Dry (psi) | 670 |
| Perpendicular to Rift, Wet (psi) | 991 |

