















SPECIFICATIONS

	GEOLOGY	Sandstone
	TYPE	100% Splitface
	PATTERN	Coursed Dimensional Ashlar 2:1 Dimensional Ashlar
	HEIGHTS	2-1/4" (20%), 5" (50%), 7-3/4" (30%)
	LENGTHS	8"-20"
	DEPTHS	3/4" to 1-1/4"
	COLORS	Beige, Brown, Buff, Salmon, Tan
	COVERAGE	
	WEIGHT	12.3 lbs. per square foot.
	FLATS	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	CORNERS	10 l/f Box, 100 l/f Crate; Crated material can exceed 20"
	NOTES	

ASTM C-97

Water Absorption %	3.8
Bulk Specific Gravity	2.4

ASTM C-170

Parallel to Rift, Dry (psi)	4115
Parallel to Rift, Wet (psi)	2612
Perpendicular to Rift, Dry (psi)	
Perpendicular to Rift, Wet (psi)	

ASTM C-99

Parallel to Rift, Dry (psi)	1912
Parallel to Rift, Wet (psi)	2054

ASTM C-880

Perpendicular to Rift, Dry (psi)	670
Perpendicular to Rift, Wet (psi)	991

