














SPECIFICATIONS

	GEOLOGY	Sandstone
	TYPE	100% Bedface
	PATTERN	2:1 Dimensional Ashlar or Coursed
	HEIGHTS	2-1/2", 5"
	LENGTHS	Thin Veneer Only: 6" - 20" (Crated or Palletized material can exceed 20")
	DEPTHS	3/4" to 1-1/4"
	COLORS	Medium grays
	COVERAGE	Available in thin veneer only.
	WEIGHT	12.5 lbs per square foot
	FLATS	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	CORNERS	10 ln/ft Box, 100 ln/ft Crate
	NOTES	Packaged assuming a tight-fit installation.

ASTM C-97

Water Absorption %	.12
Bulk Specific Gravity	2.78

ASTM C-170

Parallel to Rift, Dry (psi)	14214
Parallel to Rift, Wet (psi)	14213
Perpendicular to Rift, Dry (psi)	21814
Perpendicular to Rift, Wet (psi)	21320

ASTM C-99

Parallel to Rift, Dry (psi)	3046
Parallel to Rift, Wet (psi)	3191

ASTM C-880

Perpendicular to Rift, Dry (psi)	4351
Perpendicular to Rift, Wet (psi)	4351

