















SPECIFICATIONS

	GEOLOGY	Mica-Schist Quartz (Quartzitic Sandstone)
	TYPE	
	PATTERN	2:1 or 2:3, Sawn Course Heights Dimensional Tight-fit
	HEIGHTS	1" - 2" (~50%), 3" (~25%), 5" (~25%)
	LENGTHS	4" - 14"
	DEPTHS	3/4" to 1-1/4"
	COLORS	Gray-Grey , Silver
	COVERAGE	Available in thin veneer only.
	WEIGHT	12.7 lbs. per square foot
	FLATS	5 s/f Bag, 10 s/f Box, 90/150/180 s/f Crate
	CORNERS	5 l/f Bag, 10 l/f Box, 90/100 l/f Crate
	NOTES	Packaged assuming a tight-fit installation comprising of 50% Silver Ledgestone , 50% sawn-height jumpers. Please review the Corners Installation PDF document.

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730



GOLD QUARRY
 ANSI/NSC 373-2013
 C0290908-101



GOLD FABRICATOR
 ANSI/NSC 373-2013
 C0289215-101