















SPECIFICATIONS

| | | |
|--|-----------------|---|
|  | GEOLOGY | Mica-Schist Quartz (Quartzitic Sandstone) |
|  | TYPE | |
|  | PATTERN | 1:1 (coursed if rotated) or 2:1 Horizontal Panelized material with 2 specified/sawn heights |
|  | HEIGHTS | 8" |
|  | LENGTHS | 18" |
|  | DEPTHS | 1/2" - 1" |
|  | COLORS | Gray - Grey |
|  | COVERAGE | 1 Square foot per panel. |
|  | WEIGHT | 11 lbs. per square foot. |
|  | FLATS | 10 Panels/Box, 180 Panels/Crate |
|  | CORNERS | 5 In ft of Panels per bag |
|  | NOTES | 1 Square Foot of coverage per panel (8" x 18") |

ASTM C-97

| | |
|-----------------------|----|
| Water Absorption % | .9 |
| Bulk Specific Gravity | |

ASTM C-170

| | |
|----------------------------------|-------|
| Parallel to Rift, Dry (psi) | 18175 |
| Parallel to Rift, Wet (psi) | 31470 |
| Perpendicular to Rift, Dry (psi) | |
| Perpendicular to Rift, Wet (psi) | |

ASTM C-99

| | |
|-----------------------------|------|
| Parallel to Rift, Dry (psi) | 5584 |
| Parallel to Rift, Wet (psi) | 5502 |

ASTM C-880

| | |
|----------------------------------|------|
| Perpendicular to Rift, Dry (psi) | 3984 |
| Perpendicular to Rift, Wet (psi) | 1064 |

