















## SPECIFICATIONS

|  |                 |   |
|--|-----------------|---|
|  | <b>GEOLOGY</b>  | Limestone   |
|  | <b>TYPE</b>     | 50% Seam Face, 50% Split Face   |
|  | <b>PATTERN</b>  | 2:1 Natural Course Heights   Random Ashlar  |
|  | <b>HEIGHTS</b>  | 2" - 9" (Full Bed & Thin Veneer)  |
|  | <b>LENGTHS</b>  | Full Veneer: 8"-36"   Thin Veneer: 6" - 20"<br>(Crated or Palletized material can exceed 20") |
|  | <b>DEPTHS</b>   | 3/4" - 1 1/4" (Thin Veneer); 3"-5" Full Veneer  |
|  | <b>COLORS</b>   | Beige, Brown, Buff, Gray-Grey, Tan  |
|  | <b>COVERAGE</b> | Full Bed Depth Veneer: 35-40 Square Feet Per Ton  |
|  | <b>WEIGHT</b>   | 14.9 lbs/sq ft (Thin Veneer); 160 lbs per cubic foot (Full Veneer)                            |
|  | <b>FLATS</b>    | 10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 180 s/f Crate, 200 s/f Pallet       |
|  | <b>CORNERS</b>  | 10 l/f Box; 100 l/f Crate; 100 l/f Pallet   |
|  | <b>NOTES</b>    |   |

### ASTM C-97

|                       |      |
|-----------------------|------|
| Water Absorption %    | .31  |
| Bulk Specific Gravity | 2.83 |

### ASTM C-170

|                                  |       |
|----------------------------------|-------|
| Parallel to Rift, Dry (psi)      | 36100 |
| Parallel to Rift, Wet (psi)      | 32000 |
| Perpendicular to Rift, Dry (psi) | 35800 |
| Perpendicular to Rift, Wet (psi) | 30000 |

### ASTM C-99

|                             |      |
|-----------------------------|------|
| Parallel to Rift, Dry (psi) | 3770 |
| Parallel to Rift, Wet (psi) | 3500 |

### ASTM C-880

|                                  |      |
|----------------------------------|------|
| Perpendicular to Rift, Dry (psi) | 1780 |
| Perpendicular to Rift, Wet (psi) | 1730 |



**GOLD QUARRY**  
 ANSI/NSC 373-2013  
 C0290908-101



**GOLD FABRICATOR**  
 ANSI/NSC 373-2013  
 C0289215-101