















SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	
	PATTERN	
	HEIGHTS	Select Outcropping: 6 to 8 inches irregular, 5 to 12 inches irregular pallet-sized pieces
	LENGTHS	"1-2 man": 18" - 30" x 18" - 30" "2-3 man": 24" - 40" x 24" - 40"
	DEPTHS	5 to 12 inches
	COLORS	grays, taupes, tans, charcoal, black
	COVERAGE	
	WEIGHT	Outcroppings priced per ton
	FLATS	
	CORNERS	
	NOTES	Select, irregular, "1-2 man", "2-3 man" sizes available. Also see Graphite Country for building stone veneer versions.

ASTM C-97

Water Absorption %	.31
Bulk Specific Gravity	2.83

ASTM C-170

Parallel to Rift, Dry (psi)	36100
Parallel to Rift, Wet (psi)	32000
Perpendicular to Rift, Dry (psi)	35800
Perpendicular to Rift, Wet (psi)	30000

ASTM C-99

Parallel to Rift, Dry (psi)	3770
Parallel to Rift, Wet (psi)	3500

ASTM C-880

Perpendicular to Rift, Dry (psi)	1780
Perpendicular to Rift, Wet (psi)	1730



GOLD QUARRIER
 ANSI/NSC 373-2013
 C0290908-101



GOLD FABRICATOR
 ANSI/NSC 373-2013
 C0289215-101